

E50 COMPLIANCE DEVICE | P/N: 88001628


Summary

The E50 Compliance Device is an accessory to the E50 (sold separately). The compliance device simplifies setup for the E50 by compensating for part variation and can be used for flat and near flat contact, NOT for extreme deviation (round parts). Consider units with customizable pole geometries in these scenarios instead. Angular compliance is allowed on the X and Y axes as well as vertical compression about the Z axis. The additional flexibility also improves handling of sagging sheets ensuring the maximum performance in each application. It also imparts a dampening effect against accelerations.





Specifications

Net Weight (Compliance Device Only)	1.65 lb	0.75 kg
Pitch Forward/Backward (X-axis)	+/-4.5°	
Roll Left/Right (Y-axis)	+/-4.5°	
Yaw Clockwise/Counterclockwise (Z-axis)	Negligible Movement	
Z-axis Compression	-5mm	
X-axis or Y-axis Lateral Movement	+/-1.5mm if in compression	
Dimensions (Compliance Device Only)	80mm x 80mm x 50.67mm	




Compatible Tool Available:

E50 (sold separately)	81401264
-----------------------	----------




Installation Instructions


- Switch the E50 tool to the OFF state.
- Remove the E50 tool from preexisting mounting surfaces as required to expose top surface of the tool. Ensure dowel holes are clean. Confirm the top surface of the tool is flat and smooth.
- Insert two dowel pins into the dowel holes on the bottom of Compliance Device. Apply Thread Locking Compound on the thread of M8 Socket Head fastener.



- Install the Compliance Device on top of E50. Align two dowel pins with the dowel holes on top of E50 (Set the direction as needed). Insert dowel pins until the Compliance Device is flush against E50.



- Insert 6mm Hex Driver through the center hole on top of Compliance Device. Thread and tighten the fastener through the bottom plate into the threaded bore on top of E50. Torque the fastener to 41Nm.



- The installation of E50 Compliance Device is complete. There should be no visible gaps between the E50 tool and the Compliance Device.

